

# Super Skim Coat



*2 Colors Grey and With*

*For plastering concrete surface  
both of interior and exterior building*

**GENERAL ENGINEERING PUBLIC COMPANY LIMITED**

44/2 MOO 2 TIVANONT ROAD, BANGKADEE, MUANG, PHATHUMTHANEE 12000 THAILAND

TEL : +662 501 2020 , 501 1055 FAX : +662 501 2134

E-mail : [gel@gel.co.th](mailto:gel@gel.co.th) Homepage : [www.gel.co.th](http://www.gel.co.th)

# **SUPER SKIM COAT**

**Premixed Cement For Surface Finishing**

## **APPLICATION RANGE**

For use to plastered of precast concrete wall and can be applied on plastered wall or concrete surface and general cement surface.

## **FEATURES**

- The application thickness is approximately 1-3 mm.
- Excellent bonding to cementitious substrates.
- Good trowelability on application.
- Easy and ready to use.
- Perfectly smooth and slick surface.

## **SURFACE PREPARATION**

- Clean the surface dirt, dust-free and without any traces of oil.
- If the surface is scratched by a hole or pore shall be the repairing before the plaster.

## **WORK INSTRUCTION**

- Mix with water the ratio of 1 kg per 0.4 liter of clean water or 2.5 : 1 by volume.
- Mix by machine-mix or hand-mix until the compound is a sticky cream.
- After mixing, shall be await is about 5 minute for the chemical curing.

## **CONSUMPTION**

- Super Skim Coat one bag (25 kg) can be the plaster about 30 sq.m. at 1 mm of thickness.

## **PRECAUTIONS**

- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

## **STORAGE**

- Keep in shade and shall be avoid exposure from direct of sunshine.
- Shelf life 12 month in the sealed container.

**Packing 25 kg**



**GENERAL ENGINEERING PUBLIC COMPANY LIMITED**

44/2 MOO 2 TIVANONT ROAD, BANGKADEE, MUANG, PHATHUMTHANEE 12000 THAILAND

TEL : +662 501 2020 , 501 1055 FAX : +662 501 2134

E-mail : gel@gel.co.th Homepage : www.gel.co.th